

Mini, 1"-Round-Plug Connector, Single-Ended Cordsets, US Color Code



RS 701M...801M | RK 70M...80M



7-, and 8-Poles



Mini, 1" single-ended cordsets, male straight, 7-, and 8-poles with internal threads and molded PUR cable, US color code.

RS



Mini, 1" single-ended cordsets, female straight, 7-, and 8-poles with internal threads and molded PUR cable, US color code.


RK



Pin Assignments


Mini, 1" - Male / Female

7 poles



1 = white/black
2 = black
3 = white
4 = red
5 = orange
6 = blue
7 = green

8 poles



1 = orange
2 = blue
3 = white/black
4 = black
5 = white
6 = red
7 = green
8 = red/black

Be Certain with Belden



**Cordsets
Single-Ended**

Cordsets
Single-Ended

Mini, 1”-Round-Plug Connector, Single-Ended Cordsets, US Color Code RS 701M...801M | RK 70M...80M

Technical Data

Environmental

Degree of protection IP 67 / NEMA 6P
Operating temperature range -40°C (-40°F) / +90°C (194°F)

Mechanical


Housing / Molded body TPU, yellow
Insert TPU, yellow
Contact CuZn, gold over silver plated
Coupling nut Aluminum, anodized black

Electrical

Current rating 7 pole: 8 A
8 pole: 7 A
Voltage rating 300 V

Cable Specifications - US Color Code

Cable No.	Outer Jacket	Gauge	Jacket Color	OD	Temperature Rating	Agency Approvals
649	PUR	18AWG	Yellow	.270" (6.9 mm)	-40°C (-40°F) to +80°C (176°F)	UL: AWM 20233 / CSA: AWM I/II A/B
650	PUR	18AWG	Yellow	.292" (7.4 mm)	-40°C (-40°F) to +80°C (176°F)	UL: AWM 20233 / CSA: AWM I/II A/B

Part Number	Pins	Outer Jacket	Standard Cable Lengths	Characteristics
RS 701M-649/...F RK 70M-649/...F	7	PUR	6 F / 12 F / 15 F / 20 F / 30 F	
RS 801M-650/...F RK 80M-650/...F	8	PUR	6 F / 12 F / 15 F / 20 F / 30 F	